

# Avery Dennison® SF100 Series Paint Mask Films

Removable - Kraft

Revision: 4 Dated: 11/10/23

## Uses:

Avery Dennison® SF100 Series Paint Masks are flexible calendered vinyl with removable adhesive, which will cleanly remove from most OEM surfaces up to 1 year, when removed promptly after painting and curing cycles. SF 100-235-S can be used for high temperature bake cycles.



**Face:** Calendered

-128 - 3.4 mil (86 µm) matte white

-231 - 3.4 mil (86 µm) matte yellow

-235 - 3.2 mil (81 µm) semi gloss yellow



**Adhesive:** Clear Removable Acrylic



**Liner:** 78# Kraft



**Durability:** Up to 1 year

**Application Surfaces:** Flat

## Features:

- Dimensionally stable liner for easy converting
- Excellent UV, temperature, humidity, and salt-spray resistance
- Short Term Promotional Applications
- Easy cutting and weeding for crisp paint lines
- Removable from most OEM paints
- Clean removability when used with most paint cycles

## Conversion:

- Thermal Die-Cutting
- Roll Fed Sign-Cut
- Steel Rule Die-Cut

## Common Applications:

- Sign Stencils
- OEM Stencils
- Removable Letters

## Product Data Sheet

Page 1 of 4



Graphics  
Solutions

[www.graphics.averydennison.com](http://www.graphics.averydennison.com)  
Customer Service: 800-282-8379

# Avery Dennison® SF100 Series Paint Mask Films

Removable - Kraft

Revision: 4 Dated: 11/10/23

## Physical Characteristics:

Data represents average values where applicable, and is not intended for specification purposes.

Property	Measurement	Typical Value
Caliper, face	-128	3.4 mil (86 µm)
	-231	3.4 mil (86 µm)
	-235	3.2 mil (81 µm)
Caliper, adhesive		1.0 mil (25 µm)
Dimensional stability		<0.15" (3.8 mm)
Tensile at Yield		NA
Elongation		100% min.
Gloss	-128	matte
	-231	matte
	-235	gloss
Adhesion:	24 hr	0.2 lbs/in (35 N/m)
Flammability	Self Extinguishing	
Shelf-Life		2 years from date of manufacture (when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.)
Durability	Vertical Exposure	Up to 1 year
Min. Application Temperature		40° F (4° C)
Service Temperature		<u>SF-100 -128 &amp; 231</u> : not designed for use in conjunction with paint baking cycles. <u>SF-100-235</u> -40° to +200°F (-40° to +94°C). Yellow paint mask is able to withstand mild paint baking cycles up to +200°
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions
Compliance		<a href="#">California Proposition 65</a>
MSDS		<a href="#">MSDS Article Letter</a>

## Product Data Sheet

Page 2 of 4



Graphics  
Solutions

[www.graphics.averydennison.com](http://www.graphics.averydennison.com)  
Customer Service: 800-282-8379

# Avery Dennison® SF100 Series Paint Mask Films

Removable - Kraft

Revision: 4 Dated: 11/10/23

## Warranty:

This Warranty applies to the Product listed in this Data Sheet. All statements, technical information (including physical and chemical characteristics) and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold subject to the Purchaser's assent and agreement that Purchaser is responsible for, and has independently determined, the suitability of such products for its purposes or its customer's purposes. Avery Dennison products are warranted to be free from defects in material and workmanship (i) for two years from the date of manufacture, or (ii) from the date of manufacture until the expiration of the period stated on the specific Product Data Sheet in effect at the time of delivery.. Such time periods are subject in either case to the proper storing and application of said product, and the failure to properly store or apply the product, including without limitation the failure to follow any applicable Instructional Bulletin, negates any warranty. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited exclusively to: (a) repair or replacement of defective product without charge at Avery Dennison's plant or at the location of the product (at Avery Dennison's election), or (b) in the event repair or replacement are not commercially practical, a credit amount up to the price of the product taking into account the defect in the product in Avery Dennison's sole discretion.

THE WARRANTY EXPRESSLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. SELLER SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

AVERY DENNISON'S LIABILITY FOR DEFECTIVE PRODUCTS SHALL NOT EXCEED THE PURCHASE PRICE PAID THEREFORE BY PURCHASER AND IN NO EVENT SHALL AVERY DENNISON BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES WHETHER FORESEEABLE OR NOT, CAUSED BY DEFECTS IN SUCH PRODUCT, WHETHER SUCH DAMAGE OCCURS OR IS DISCOVERED BEFORE OR AFTER REPLACEMENT OR CREDIT, AND WHETHER OR NOT SUCH DAMAGE IS CAUSED BY AVERY DENNISON'S NEGLIGENCE.

All sales and contracts for sale of Products are subject to Purchaser's assent and agreement to this Warranty. Avery Dennison hereby objects to any terms or conditions contained in any purchase order or other communication of any kind from the Purchaser that is conflicting, inconsistent or additional to this Agreement.

## Product Data Sheet

Page 3 of 4



Graphics  
Solutions

[www.graphics.averydennison.com](http://www.graphics.averydennison.com)  
Customer Service: 800-282-8379

# Avery Dennison® SF100 Series Paint Mask Films

Removable - Kraft

Revision: 4 Dated: 11/10/23

## Colors Cross Reference:

SF100 Series Name	Vertical Durability Zone 1 Years	SF100 Series Name	Vertical Durability Zone 1 Years
SF100-128-S White Paint Mask	1	SF100-231-S Yellow Paint Mask	1
		SF100-235-S High Bake Yellow Paint Mas	1

**NOTE:** Some color fade may occur in severe environmental areas. Reference IB 1.30 for durability guidelines.

Revisions are italicized

Avery Dennison and Easy Apply are registered trademarks of Avery Dennison Corporation

## Product Data Sheet

Page 4 of 4



Graphics  
Solutions

[www.graphics.averydennison.com](http://www.graphics.averydennison.com)  
Customer Service: 800-282-8379