

Avery Dennison® Auravate Decorative Window Films

- River Waters, Oak Frost, Sandstone

Revision: 0

Dated: 08/20/24

Uses:

Avery Dennison® Auravate Decorative Window films River Waters, Oak Frost and Sandstone are Architectural Decorative Vinyl Films applied as a retrofit on existing glass to provide an enhanced decorative upgrade to plain, clear glass at a fraction of the cost of glass replacement. For use on architectural doors, windows and other flat glass applications.



Face: River Waters: 4 mil Vinyl
Oak Frost: 4 mil Vinyl
Sandstone: 5 mil Vinyl



Adhesive: Clear Pressure Sensitive



Release Liner: Silicone Coated PET
Sandstone: 3 mil (75 µm)
River Water & Oak Frost: 1.2 mi (30 µm)

Application Surfaces:

Flat Glass
River Waters: Interior
Oak Frost & Sandstone: Interior/Exterior

Features:

- Ideal for architectural applications requiring privacy or visual upgrades
- Premium tactile finish
- Outstanding durability and performance
- Clear silicone coated release liner for optimal sample viewing
- Easy to install
- Excellent dimensional stability
- Excellent durability
- Designs that enhance plain glass

Conversion:

- Cut out of box
- Cut with Film Handler
- Trim on glass
- Wet-apply

Common Applications:

- Decorative Aesthetics
- Privacy
- Partitions/Movable SmoothGlass Walls
- Bathrooms
- Conference Rooms

Product Data Sheet

Page 1 of 4



Avery Dennison® Auravate Decorative Window Films

- River Waters, Oak Frost, Sandstone

Revision: 0

Dated: 08/20/24

Physical Characteristics:

Property	Measurement	Typical Value
Caliper, face		River Waters: 4 mil (101 µm) Oak Frost: 4 mil (101 µm) Sandstone: 5 mil (127 µm)
Caliper, adhesive		0.7 - 0.87 mil (18 - 22 µm)
Flammability	ASTM E84	Class A
Shelf-Life		2 years from date of manufacture (when stored at the following temperatures and humidity conditions 68°-77° F (20° - 25° C) and 50±5% R. H.)
Durability	Vertical Exposure	Reference Expected Durability section in this data sheet
Min. Application Temperature		40° F (4° C)
Service Temperature		-50° to 180°F (-45° to 82° C) (Reasonable range of temperatures which would be expected under normal environmental conditions).
Chemical resistance		Avoid ammonia based cleaners

Data represents average values where applicable, and is not intended for specification purposes.

Related Documents:

The following Avery Dennison literature will provide necessary information to the user for proper application, storage, and other requirements and is available upon request from your Avery Dennison representative or from the Avery Dennison website (www.graphics.averydennison.com).

Document Title	Reference Number
Installation and Maintenance of Avery Dennison Architectural Window Film	Instructional Bulletin 7.00

Expected Durability

Vertical Durability applications are noted in the chart below. Samples are available from samples.graphics@averydennison.com, or through your distribution service contact.

Film	Application Location	Warranted Durability Zone 1 Vertical
River Waters	Interior & Perimeter	5 years
Oak Frost	Interior/Exterior & Perimeter	5 years interior 3 years exterior
Sandstone	Interior/Exterior & Perimeter	5 years interior 3 years exterior

Product Data Sheet

Page 2 of 4



Avery Dennison® Auravate Decorative Window Films

- River Waters, Oak Frost, Sandstone

Revision: 0

Dated: 08/20/24

Optical and Solar Properties **

Glass	Applied on 1/8" (3mm) clear glass		
Product	River Waters	Oak Frost	Sandstone
Visible Light Transmitted %	58%	35%	53%
Visible Light Reflected (Int) %	8%	--	70%
Ultraviolet Block %	52%	98%	78%
Total Solar Energy Reflected %	7%	--	7%
Total Solar Energy Transmitted %	76%	--	76%
Shading Coefficient (SC)	0.93	--	0.93

**Performance results are calculated on 3 mm glass using NFRC methodology and LBNL Window 5.2 software, and are subject to variations in process conditions within industry standards and are only intended for estimating purposes.

Special Considerations:

Because of the unique properties and varieties of glass, special considerations must be considered for windows and Auravate Decorative Film Applications. Avery Dennison accepts no liability for glass breakage.

- Glass absorbs heat when exposed to sunlight. The degree of absorption across windows can vary because of shading, heating, and cooling ventilation, and insulation from window frames. These temperature differences across the window produce stress, which can cause glass breakage. The ability of glass to resist breakage because of temperature stress is affected by window size, glass thickness, glass treatments, quality, and design.
- Window cleaning methods also vary, from the type of cleaners used, to the washing methods employed. Specific chemicals used in window cleaners may affect the adhesion of pressure-sensitive graphics. Power washing methods may impact the adhesion of graphics, if the water pressure or temperature exceeds the graphics adhesion capability.

Revisions are italicized

Avery Dennison is registered trademark of Avery Dennison Corporation

Product Data Sheet

Page 3 of 4



Avery Dennison® Auravate Decorative Window Films

- River Waters, Oak Frost, Sandstone

Revision: 0

Dated: 08/20/24

Warranty:

This Warranty applies to the Product listed in this Data Sheet. All statements, technical information (including physical and chemical characteristics) and recommendations about Avery Dennison products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold subject to the Purchaser's assent and agreement that Purchaser is responsible for, and has independently determined, the suitability of such products for its purposes or its customer's purposes. Avery Dennison products are warranted to be free from defects in material and workmanship (i) for two years from the date of manufacture, or (ii) from the date of manufacture until the expiration of the period stated on the specific Product Data Sheet in effect at the time of delivery. Such time periods are subject in either case to the proper storing and application of said product, and the failure to properly store or apply the product, including without limitation the failure to follow any applicable Instructional Bulletin, negates any warranty. It is expressly agreed and understood that Avery Dennison's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited exclusively to: (a) repair or replacement of defective product without charge at Avery Dennison's plant or at the location of the product (at Avery Dennison's election), or (b) in the event repair or replacement are not commercially practical, a credit amount up to the price of the product taking into account the defect in the product in Avery Dennison's sole discretion.

THE WARRANTY EXPRESSLY SET FORTH ABOVE IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR USE AND/OR NON-INFRINGEMENT. SELLER SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND MANUALLY SIGNED BY AN OFFICER OF AVERY DENNISON.

AVERY DENNISON'S LIABILITY FOR DEFECTIVE PRODUCTS SHALL NOT EXCEED THE PURCHASE PRICE PAID THEREFORE BY PURCHASER AND IN NO EVENT SHALL AVERY DENNISON BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES WHETHER FORESEEABLE OR NOT, CAUSED BY DEFECTS IN SUCH PRODUCT, WHETHER SUCH DAMAGE OCCURS OR IS DISCOVERED BEFORE OR AFTER REPLACEMENT OR CREDIT, AND WHETHER OR NOT SUCH DAMAGE IS CAUSED BY AVERY DENNISON'S NEGLIGENCE.

All sales and contracts for sale of Products are subject to Purchaser's assent and agreement to this Warranty. Avery Dennison hereby objects to any terms or conditions contained in any purchase order or other communication of any kind from the Purchaser that is conflicting, inconsistent or additional to this Agreement.

Product Data Sheet

Page 4 of 4

